

**QUOTATION FOR FIXING OF KOTA
STONE IN GROUND FLOOR OF ARYABHATT BUILDING**

Army Public School, Dagshai invites quotations from interested parties/firms for fixing of kota stone in ground floor of Aryabhata Building as under:-

| <u>Work</u> | <u>Area</u> | <u>Rate</u> | <u>Amount</u> |
|--|-------------|-------------|---------------|
| Fixing of kota stone by breaking the existing floor on ground floor of Aryabhata Building. | 4800 Sqft | | |
| GST + Labour | | | |
| Total | | | |

Terms and conditions

1. The work is required to be completed within the period of 45 days from the date of commencement.
2. The envelope containing tender should be marked "**providing & fixing of kota stone**". The material of work must be high standard thickness 20mm or as per the school requirement. The successful contractor will get samples of material approved before commencement of work.
3. Providing and fixing of Kota Stone will be carried out as under:-
 - (a) **Stone Slabs**. The slab shall be of 20 mm thickness or school requirement, hard, sound, dense and homogeneous in texture, free from cracks, decay, weathering and flaws. They shall be hand or machine cut to the requisite thickness/size as indicated or directed by second party and they shall be of uniform colour. The slabs shall have the top (exposed) face polished before being brought to site.
 - (b) **Dressing of Slabs**. Every slab shall be cut to the required size, shape and fine chisel dressed on the sides to the full depth so that a straight edge laid along the side of the stone shall be in full contact with it. The sides (edges) shall be table rubbed with coarse sand or

(c) **Preparation of Surface and Laying** - Sub-grade concrete or the RCC slab on which the slabs are to be laid shall be cleaned, wetted and mopped. The bedding for the slabs shall be with cement mortar and the thickness as indicated or directed by second party will be in the ratio of cement mortar 1:4 (1 cement : 4 coarse sand) of average thickness 20mm base course/cushioning layer shall be cleaned wetted and mopped.

(d) The kota stone/slab shall be laid in the following manner:-

(i) Mortar of the specified mix shall be spread under the area of each slab, roughly to the average thickness as indicated as given above.

(ii) The slab shall be washed and cleaned before laying. It shall be laid on top, pressed, tapped with wooden mallet and brought to level with the adjoining slabs. It shall be lifted and laid aside.

(iii) The top surface of the mortar shall then be corrected by adding fresh mortar at hollows. The mortar is allowed to harden a bit and cement slurry of honey like consistency shall be spread over the same at the rate of 4 kg of cement per square metre.

(iv) The slab to be paved shall be lowered gently back in position bedded in level. Subsequent slabs shall be laid in the same manner and joints between adjacent slabs shall be as thin as possible and run in straight line.

(v) After each slab has been laid, surplus cement grout coming out of the joints of the slabs shall be cleaned off. The surface of the flooring as laid shall be true to levels, lines and shapes as instructed by the second party.

(e) Slabs which are fixed in the floor adjoining the wall shall enter not less than twelve (12) mm under the plaster skirting or dado. The junction between wall plaster and the floor shall be finished neatly and without waviness.

(f) **Curing, Polishing and Finishing** The floor shall be kept wet for a minimum period of seven (7) days. The surface shall thereafter be grounded evenly with machine fitted with fine grade blocks. The final grinding with machine fitted with the finest grade grit blocks shall be carried out the day after the first grinding described above or before handing over the floor, as ordered by the Second party.

(g) For small areas or where circumstances so require, hand polishing may be permitted in lieu of machine polishing after laying. For hand polishing the following Carborundum stones shall be used. 1st grinding - Medium Grade Stone (No.8) Final Grinding - Fine Grade (No. 120)

(h) If any slab is disturbed or damaged, it shall be refitted or replaced, properly jointed and polished. The finished floor shall not sound hollow when tapped with wooden mallet.

The tender are subject to the approval by the board of officers detailed by the Chairman , APS Dagshai, who do not bind themselves to accept the lowest quotation or to give reason for rejecting any quotation.

5. Prior to acceptance of the tender the undersigned reserves the right to call for sample and the contractor shall be liable to supply the same. The successful contractor will start the work after getting the approval of sample/material by the board. No material shall be supplied by APS Dagshai.
6. Conditional quotation will not be accepted.
7. The contractor will have to arrange water and electricity etc from his own sources. If contractor wants to use water and electricity from the school, the contractor will have to pay charges of the same at the rate of 2% of contract. The same will be deducted from final payment of the bill.
8. The security amount will be 5% of contract amount, which is required to be deposited by the successful contractor and security amount will be refunded without interest after one year of completion of the contract/final payment. If the contractor fails to execute any work entrusted to him within prescribed time, Principal APS, Dagshai will be at liberty to get the work executed through any other agency at risk and cost of the contractor & if the security falls short, the contractor will pay the difference. The payment will be made as per school rule.
9. Income tax, TDS and other taxes as applicable under rules will be deducted from the bills of the contractor. You are requested to mentioned GST No and PAN No in tender Form. Photocopy of GST Certificate will be mandatory to be attached with tender documents without which tender will be rejected.
10. The payment of work will be made on actual measurement of work on ground after getting the satisfactory certificate from the board in accordance with the specification/sample of the work executed at sites by the contractor. No interest will be paid on delay payment.
11. On acceptance of the quotation it will become a contract and shall be bound by terms and conditions of the quotation. Interested contractors can visit the site between 10 am to 5 pm in any working days.
12. The board detailed by the school authorities will inspect the material of tiles and other items as per approved by the Board of Officers.
13. In case, you are interested, you may send your quotation in sealed envelope to reach the school latest by 16 May 2024 or dropped in Tender Box placed at gate of school at APS Dagshai.



Principal
APS Dagshai

GENERAL INFORMATION

| | | |
|----|--|--|
| 1. | Name of Applicant / Company | |
| 2. | Address for correspondence | |
| 3. | Contact Person: _____ Telephone No. _____ Mobile _____ Email ID _____ | |
| 4. | Type of Organization: (a) An individual (b) A proprietary firm (c) A firm in partnership (d) Company | |
| 5. | Place and Year of Incorporation | |
| 6. | GST No. | |
| 7. | PAN No | |

**DETAILS OF ITEMS/SERVICES SUPPLIED/PROVIDED DURING THE LAST 3 YEARS
(DETAILS TO BE FURNISHED IN THE FOLLOWING FORMAT)**

| Sr. No. | Name of contract | Name & Address of the client | Remarks |
|---------|------------------|------------------------------|---------|
| | | | |
| | | | |
| | | | |

TURN OVER AND CAPITAL FOR OF LAST THREE YEARS:

| S. No. | Financial Year | Capital of firm | Turnovers |
|--------|----------------|-----------------|-----------|
| 1 | 2021 - 2022 | | |
| 2 | 2022 - 2023 | | |
| 3 | 2023 - 2024 | | |

In addition to the above the applicant has to submit the following documents/ Information:

1. Copy of valid GST Number.
2. Copy of Balance sheet
3. Copy of PAN.

Notes

Tender will be rejected without photocopy of GST certificate , Tender cost & Earnest Money .

जीएसटी प्रमाण पत्र की फोटोकॉपी, निविदा लागत और बयाना राशि के बिना निविदा खारिज कर दी जाएगी/

Seal and Signature of Applicant